

Specifications

備注(Remark)

1. 材料(Material)

膠芯:PA9T/LCP+30%G.F UL94V-0, 顏色:黑色

Housing:PA9T/LCP+30%G.F UL94V-0, Color:Black

端子:黃銅

Contact:Brass

2. 特性(characteristics):

額定電流:0.75AMP

Rating Current:0.75AMP

接觸阻抗:20mΩ Max

Contact Resistance:20mΩ Max

絕緣阻抗:1000MΩ Min

Insulating Resistance:1000 MΩ Min

耐電壓: AC 500V/分钟

Withstanding Voltage:AC 500V/Minute

溫度範圍: -40° C to+105° C

Temperature Range: -40° C to+105° C

PH100-22PXXXXXXXXXX1

L=A+B+C




PH100-22SXXXXXXXXXX1

L=B+C+D+(W-1.0)/2



PH100-22SXXXXXXXXXX2

L=B+C+D+(W-1.0)/2



Mating With/配對母座:





Recommended P.C.B Layout



Users can customize
此高度可定制



Recommended P.C.B Layout



TYPE1

TYPE2

Dimension antitheses list			
ITEM	A	B	C
Standard	1.80	1.80	
Alternate			

H
1.0 2.0
1.5 3.0

Dimension antitheses list					
ITEM	B	D	C	W	H
Standard	1.80	0.10		5.00	1.0 2.0
Alternate					1.5 3.0

PH100-22

X

XX

XX

XXX

X

X

X

Contact Shape:
P: Straight
S: SMT

No. Of Pins
Per Row
02~50P

Contact Plating
Full Of Gold
G0=0.8u"
~

G9=30u"

S1=Ordinary Tin Plated

S2=Matte Tin Plated

S3=Tin-plated High-temperature

Length Of
Terminal

Packing
A: PE Bag
R: Tape & Reel
T: Tube
D: Tube+CAP
E: Tray

Journal Number
1: Type1 (without Post)
2: Type2 (with Post)

Width
Number
A: 2.30
B: 3.20