

Specifications

備注 (Remark)

1. 材料 (Material)

膠芯: PA9T / LCP+30%G.F UL94V-0, 顏色: 黑色

Housing: PA9T/LCP+30%G.F UL94V-0, Color: Black

端子: 磷銅

Contact: Phosphor Bronze

2. 特性 (characteristics):

額定電流: 3.00AMP

Rating Current: 3.00AMP

接觸阻抗: 20mΩ Max

Contact Resistance: 20mΩ Max

絕緣阻抗: 1000MΩ Min


Insulating Resistance: 1000 MΩ Min

耐電壓: AC 1000V/分钟


Withstanding Voltage: AC 1000V/Minute

溫度範圍: -40° C to +105° C


Temperature Range: -40° C to +105° C




BF254-32PXXX850X1



BF254-32PXXX850X2




BF254-32RXXX850X1







BF254-32RXXX850X2

Mating With/配對公座:







F




FEMALE HEADER







TYPE1



TYPE1



TYPE2



TYPE2

BF254-32

X

XX

XX

850

X

X

Contact Shape:
P: Straight
R: Right Angle

No. Of Pins Per Row
02~40P

Contact Plating
Full Of Gold
G0=0.8u"
G9=30u"
S1=Ordinary Tin Plated
S2=Matte Tin Plated
S3=Tin-plated High-temperature

Packing
A: PE Bag
R: Tape & Reel
T: Tube
D: Tube+CAP
E: Tray

Journal Number
1: Type1 (without Post)
2: Type2 (with Post)